

TECHNICAL DATA

# RSE300 and RSE600 Infrared Cameras



## Mounted infrared cameras for research, science and engineering

- **MATLAB®** and **LabVIEW®** software compatibility allows users to integrate infrared data, images and videos to support R&D analysis
- 320x240 and 640x480 resolution options
- See the details you need with **optional smart lenses**: 2x and 4x telephoto, wide angle and macro lenses
- Optimize images, generate customizable reports and export images to the format of your choice with **SmartView® desktop software**
- Eliminate potential for mis-diagnosis with automatically focused images throughout your field of view with **MultiSharp™ Focus**

## SUPERIOR IMAGE QUALITY

### SPATIAL RESOLUTION

**RSE300**  
1.85 mRad  
**RSE600**  
0.93 mRad

### RESOLUTION

**RSE300**  
320x240  
**RSE600**  
640x480


### FIELD OF VIEW

**RSE300**  
34 °H x 25.5 °V  
**RSE600**  
34 °H x 25.5 °V

## 100 % Focused—Every object. Near and far. MultiSharp™ Focus.



Manual focus



MultiSharp Focus, available on the RSE300 and RSE600 Infrared Cameras

**育億企業股份有限公司**

**YO IE ENTERPRISE CORP., LTD**

Tel: +886-2-7746-3368  
Fax: +886-2-2999-1178

E-mail: [sales@yoie.com.tw](mailto:sales@yoie.com.tw)  
Web: [www.yoie.com.tw](http://www.yoie.com.tw)

New Taipei City 241, Taiwan

地址: 241 新北市三重區重新路五段 609 巷 16 號 8 樓之 10

Add: 8F.-10, No.16, Ln. 609, Sec. 5, Chongxin Rd., San-chong Dist.,



## Detailed specifications

	RSE300	RSE600
<b>Key Features</b>		
Infrared Resolution <sup>1</sup>	320x240 (76,800 pixels)	640x480 (307,200 pixels)**
<b>IFOV with standard lens (spatial resolution)</b>	1.85 mRad	0.93 mRad
Field of view	34 °H x 25.5 °V	34 °H x 25.5 °V
Minimum focus distance	15 cm (approx. 6 in)	
Camera focus options	Focus is adjusted in SmartView® desktop software	
MultiSharp™ Focus	Yes, focused near and far, throughout the field of view	
IR-Fusion® technology	Yes, in SmartView® desktop software. Five modes of image blending (AutoBlend™ mode, Picture-in-Picture (PIP), IR/Visible alarm, Full IR, Full visible light) add the context of the visible details to your infrared image	
Interfaces for image/data transfer	Supported in camera data ports: GigE Vision	
Thermal sensitivity (NETD)	≤ 0.030 °C at 30 °C target temp (30 mK)*	≤ 0.040 °C at 30 °C target temp (40 mK)*
Filter mode (NETD improvement)	Yes	
<b>Level and span</b>	Smooth auto and manual scaling, in SmartView® desktop software	
Fast auto toggle between manual and auto modes	Yes, in SmartView® desktop software	
Fast auto-rescale in manual mode	Yes, in SmartView® desktop software	
Minimum span (in manual mode)	0.1 °C (0.18 °F), in SmartView® desktop software	
Minimum span (in auto mode)	<1.0 °C (<1.8 °F), in SmartView® desktop software	
Built-in digital camera (visible light)	5 megapixel industrial performance	
Frame rate	60 Hz or 9 Hz versions	
Digital zoom	Variable up to 16x in SmartView® desktop software	
<b>Data storage and image capture</b>		
Memory options	Connect to SmartView® desktop software for storage to device	
Image capture, review, save mechanism	Capture, save and analyze images in SmartView® desktop software	
Image file formats	Non-radiometric (.bmp) or (.jpeg) or fully-radiometric (.is2); no analysis software required for non-radiometric (.bmp, .jpg and .avi) files	
Software	SmartView® desktop software—full analysis and reporting software Compatible with MATLAB® and LabVIEW® software	
Export file formats with SmartView® desktop software	Bitmap (.bmp), GIF, JPEG, PNG, TIFF	
Voice annotation	Yes, in SmartView® desktop software	
IR PhotoNotes™	Yes, in SmartView® desktop software	
Text annotation	Yes, in SmartView® desktop software	
Video recording	Radiometric, in SmartView® desktop software, with exports to standard non-radiometric formats	
File formats video	Non-radiometric (MPEG-encoded .AVI) and fully-radiometric (.IS3), in SmartView® software	
Remote display viewing	Yes, see the live stream of the camera display on your PC, or TV monitor, via Ethernet cable to SmartView® desktop software	
Remote control operation	Yes, through SmartView® desktop software	
<b>Temperature measurement</b>		
Temperature measurement range (not calibrated below -10 °C)	-10 °C to +1200 °C (14 °F to +2192 °F)	
Accuracy	± 2 °C or ± 2 %, whichever is greater	
Autocapture	Yes, in SmartView® desktop software	
Reflected background temperature compensation	Yes, in SmartView® desktop software	
Transmission correction	Yes, in SmartView® desktop software	
<b>Color palettes</b>	Available through IR-Fusion® technology in desktop software	
Standard palettes	8: Ironbow, Blue-Red, High Contrast, Amber, Amber Inverted, Hot Metal, Grayscale, Grayscale Inverted	
Ultra Contrast™ palettes	8: Ironbow Ultra, Blue-Red Ultra, High Contrast Ultra, Amber Ultra, Amber Inverted Ultra, Hot Metal Ultra, Grayscale Ultra, Grayscale Inverted Ultra	

\*Best possible

\*\*Option to output 320x240 infrared data through GigE Vision

<sup>1</sup>These products are controlled under ECCN 6A003.B.4.B and an export license is needed for certain destinations. Please see RS1 controls for licensing requirements.

2 Fluke Corporation RSE300 and RSE600 Infrared Cameras

**育億企業股份有限公司**

**YO IE ENTERPRISE CORP., LTD**

Tel: +886-2-7746-3368  
Fax: +886-2-2999-1178

E-mail: [sales@yoie.com.tw](mailto:sales@yoie.com.tw)  
Web: [www.yoie.com.tw](http://www.yoie.com.tw)

New Taipei City 241, Taiwan

地址: 241 新北市三重區重新路五段 609 巷 16 號 8 樓之 10

Add: 8F.-10, No.16, Ln. 609, Sec. 5, Chongxin Rd., Sanchong Dist.,



免費聲明 資料僅供參考，若有與原廠不合之處，請以原廠規格為準，且不供任何證明文件之用

**Detailed specifications (continued)**

	RSE300	RSE600
<b>Key Features</b>		
Color alarms (temperature alarms)	Yes, in SmartView® desktop software—high temperature, low temperature, and isotherms (within range)	
Infrared spectral band	8 µm to 14 µm (long wave)	
Operating temperature	-10 °C to +50 °C (14 °F to 122 °F)	
Storage temperature	-20 °C to +50 °C (-4 °F to 122 °F)	
Relative humidity	10 % to 95 % non-condensing	
Center-point temperature measurement	Yes, in SmartView® desktop software	
Spot temperature	Yes, in SmartView® desktop software—hot and cold spot markers	
User-definable spot markers	Unlimited user-definable spot markers, in SmartView® desktop software	
Center box	Expandable—contractible measurement box with MIN-MAX-AVG temp display, in desktop software	
Electromagnetic compatibility	EN 61326-1:2013 IEC 61326-1:2013; (Industrial)	
US FCC	CFR 47, Part 15 Subpart B Class A	
Vibration	IEC 60068-2-26 (sinusoidal vibration): 3G, 11–200 Hz, 3 axis.	
Shock	IEC 60068-2-27 (mechanical shock): 50G, 6 ms, 3 axis.	
Size (HxWxL)	8.3 cm x 8.3 cm x 16.5 cm (3.3 in x 3.3 in x 6.5 in)	
Weight	1 kg (2.2 lbs)	
Enclosure rating	IEC 60529: IP67 (protected against dust, limited ingress; protection against water spray from all directions)	
Warranty	Two years (standard), extended warranties are available	
Recommended calibration cycle	Two years (assumes normal operation and normal aging)	
Supported languages	Czech, Dutch, English, Finnish, French, German, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, and Turkish	

**Ordering information**

- FLK-RSE300 60Hz Thermal Imager; 320x240
- FLK-RSE300 9Hz Thermal Imager; 320x240
- FLK-RSE300 9Hz/CH Thermal Imager; 320x240; 9 Hz, China
- FLK-RSE300 60Hz/JP Thermal Imager; 320x240; 60 Hz, Japan
- FLK-RSE600 60Hz Thermal Imager; 640x480
- FLK-RSE600 9Hz Thermal Imager; 640x480
- FLK-RSE600 9Hz/CH Thermal Imager; 640x480; 9 Hz, China
- FLK-RSE600 60Hz/JP Thermal Imager; 640x480; 60 Hz, Japan

**What's included**

Infrared camera with standard infrared lens; AC power supply; Ethernet cable; Antenna

Available by free download: SmartView® desktop software and user manual

Software can be downloaded at [www.fluke.com/smartviewdownload](http://www.fluke.com/smartviewdownload)

**Optional accessories**

- FLK 0.75X WIDE LENS Infrared Wide Angle Lens
- FLK 2X LENS Infrared Telephoto Lens (2X magnification)
- FLK 4X LENS Infrared Telephoto Lens (4X magnification)
- FLK MACRO LENS Infrared Macro Lens
- BOOK-ITP Introduction to Thermography Principles Book
- FLK-RSE-MB Mounting bracket
- FLK-RSE-STAND RSE Stand

Visit your local Fluke website or contact your local Fluke representative for more information.



**Fluke. Keeping your world up and running.®**

**Fluke Corporation**  
PO Box 9090, Everett, WA 98206 U.S.A.  
**Fluke Europe B.V.**  
PO Box 1186, 5602 BD Eindhoven, The Netherlands

Modification of this document is not permitted without written permission from Fluke Corporation.

**For more information call:**  
In the U.S.A. (800) 443-5853 or Fax (425) 446-5116  
In Europe/M-East/Africa +31 (0)40 267 5100 or Fax +31 (0)40 267 5222  
In Canada (800)-36-FLUKE or Fax (905) 890-6866  
From other countries +1 (425) 446-5500 or Fax +1 (425) 446-5116  
Web access: <http://www.fluke.com>

©2017, 2018 Fluke Corporation. Specifications subject to change without notice. 5/2018 6009950d-en

3 Fluke Corporation RSE300 and RSE600 Infrared Cameras

**育億企業股份有限公司**

**YO IE ENTERPRISE CORP., LTD**

Tel: +886-2-7746-3368  
Fax: +886-2-2999-1178

E-mail: [sales@yoie.com.tw](mailto:sales@yoie.com.tw)  
Web: [www.yoie.com.tw](http://www.yoie.com.tw)

New Taipei City 241, Taiwan

地址: 241 新北市三重區重新路五段 609 巷 16 號 8 樓之 10

Add: 8F.-10, No.16, Ln. 609, Sec. 5, Chongxin Rd., Sanchong Dist.,

