

# R&S® ESH3-Z6

## V-Network

For measuring disturbance voltage and susceptibility in low-impedance power supply networks



  
**ROHDE & SCHWARZ**

宥億企業股份有限公司

YO IE ENTERPRISE CORP., LTD

Tel: +886-2-7746-3368  
Fax: +886-2-2999-1178

E-mail: [sales@yoie.com.tw](mailto:sales@yoie.com.tw)  
Web: [www.yoie.com.tw](http://www.yoie.com.tw)

New Taipei City 241, Taiwan

地址: 241 新北市三重區重新路五段 609 巷 16 號 8 樓之 10

Add: 8F.-10, No.16, Ln. 609, Sec. 5, Chongxin Rd., Sanchong Dist.,



Product Brochure | Version 05.00

免責聲明 資料僅供參考，若有與原廠不合之處，請以原廠規格為準，且不供任何證明文件之用

# R&S®ESH3-Z6

## V-Network

### At a glance

The R&S®ESH3-Z6 single-phase V-network with a simulating impedance of  $5 \mu\text{H} \parallel 50 \Omega$  meets the requirements of EN 55025/CISPR 25 as well as MIL-STD-461<sup>1)</sup> DEF-STAN 59-411 and DO-160 in the frequency range from 100 kHz to 200 MHz.

The R&S®ESH3-Z6 is rated for a continuous current of up to 100 A and can handle surges of up to 500 A for a maximum of 30 s.

The R&S®ESH3-Z6 V-network comes with a calibration report for the voltage division factor.

#### Design

The R&S®ESH3-Z6 V-network has screw terminals with a large contact area for low-impedance connection to the equipment under test (EUT) and the power supply using cable lugs. Plastic covers on both connections protect against accidental contact.

#### Key facts

- 0.1 MHz to 200 MHz
- Continuous current of up to 100 A
- Calibration in line with CISPR 25: 2016 (Edition 4)

<sup>1)</sup> The current MIL-STD-461 standard requires an impedance of  $50 \mu\text{H} \parallel 50 \Omega$ . A possible alternative for CE101 and CE102 testing is  $5 \mu\text{F} \parallel 50 \Omega$ , e.g. for smaller platforms (power distribution less than 50 m) such as fighter aircraft.

宥億企業股份有限公司

YO IE ENTERPRISE CORP., LTD

Tel: +886-2-7746-3368  
Fax: +886-2-2999-1178

E-mail: [sales@yoie.com.tw](mailto:sales@yoie.com.tw)  
Web: [www.yoie.com.tw](http://www.yoie.com.tw)

New Taipei City 241, Taiwan

地址: 241 新北市三重區重新路五段 609 巷 16 號 8 樓之 10

Add: 8F.-10, No.16, Ln. 609, Sec. 5, Chongxin Rd., Sanchong Dist.,



免責聲明 資料僅供參考，若有與原廠不合之處，請以原廠規格為準，且不供任何證明文件之用

# Specifications

Specifications	
Frequency range	0.1 MHz to 200 MHz
Simulating impedance	5 $\mu$ H    50 $\Omega$
Max. permissible error limits (in line with CISPR25)	$\pm$ 20% (magnitude)
Max. permissible continuous current	100 A
Max. permissible continuous current (up to $T_a = +35^\circ\text{C}$ )	115 A
Max. permissible short-time current (up to 30 s)	500 A
<b>Max. permissible operating voltage</b>	
DC	600 V
AC	250 V
AC supply frequency range	0 Hz to 440 Hz
<b>Connectors</b>	
Power supply	M8 screw terminal
EUT	M8 screw terminal
Ground	2 x M8 screw terminals
Reference ground	uninsulated baseplate for screwing on ground plane
RF connector	N female
<b>General data</b>	
Operating temperature range	0°C to +50°C
Storage temperature range	-25°C to +70°C
Dimensions (W x H x D)	122 mm x 128 mm x 322 mm (4.8 in x 5.04 in x 12.7 in)
Weight	1.9 kg (4.19 lb)
Electrical safety	in line with EN 61010-1, see notes in manual

# Ordering information

Designation	Type	Order number
V-network	R&S®ESH3-Z6	836.5016.52
<b>Accessories supplied</b>		
Cable lugs (4 x), calibration report for voltage division factor		

宥億企業股份有限公司

YO IE ENTERPRISE CORP., LTD

Tel: +886-2-7746-3368

Fax: +886-2-2999-1178

地址: 241 新北市三重區重新路五段 609 巷 16 號 8 樓之 10

E-mail: sales@yoie.com.tw

Web: www.yoie.com.tw

Add: 8F.-10, No.16, Ln. 609, Sec. 5, Chongxin Rd., Sanchong Dist.,

New Taipei City 241, Taiwan



免責聲明 資料僅供參考，若有與原廠不合之處，請以原廠規格為準，且不供任何證明文件之用

## Service that adds value

- | Worldwide
- | Local and personalized
- | Customized and flexible
- | Uncompromising quality
- | Long-term dependability

## Rohde & Schwarz

The Rohde & Schwarz electronics group offers innovative solutions in the following business fields: test and measurement, broadcast and media, secure communications, cybersecurity, monitoring and network testing. Founded more than 80 years ago, the independent company which is headquartered in Munich, Germany, has an extensive sales and service network with locations in more than 70 countries.

[www.rohde-schwarz.com](http://www.rohde-schwarz.com)

## Sustainable product design

- | Environmental compatibility and eco-footprint
- | Energy efficiency and low emissions
- | Longevity and optimized total cost of ownership

Certified Quality Management

ISO 9001

Certified Environmental Management

ISO 14001

# 育億企業股份有限公司

# YO IE ENTERPRISE CORP., LTD

Tel: +886-2-7746-3368

Fax: +886-2-2999-1178

地址: 241 新北市三重區重新路五段 609 巷 16 號 8 樓之 10

E-mail: [sales@yoie.com.tw](mailto:sales@yoie.com.tw)

Web: [www.yoie.com.tw](http://www.yoie.com.tw)

Add: 8F.-10, No.16, Ln. 609, Sec. 5, Chongxin Rd., Sanchong Dist.,

New Taipei City 241, Taiwan



免責聲明 資料僅供參考，若有與原廠不合之處，請以原廠規格為準，且不供任何證明文件之用

R&S® is a registered trademark of Rohde & Schwarz GmbH & Co. KG

Trade names are trademarks of the owners

PD 0758.1535.12 | Version 05.00 | April 2019 (jr)

R&S®ESH3-Z6 V-Network

Data without tolerance limits is not binding | Subject to change

© 2006 - 2019 Rohde & Schwarz GmbH & Co. KG | 81671 Munich, Germany



0758.1535.12