

# EA-PS 9000 T 320 W - 1500 W



桌面式可编程直流电源

Programmable desktop DC Power supplies

A

B

C

D

E



EA-PS 9080-60 T



- 宽范围输入电压90...264 V, 带主动式PFC
- 效率高达 92%
- 输出功率: 0...320 W 至0...1500 W
- 输出电压: 0...40 V 至 0...500 V
- 输出电流: 0...4 A 至 0...60 A
- 灵活的功率调整输出级
- 监测功能 (OVP, OCP, OPP)
- 过温保护 (OT)
- 触摸屏显示器, 显示数值、状态与通知
- 标配USB端口, 可以选择以太网 & 模拟端口 (所有接口都电隔离)
- 符合SELV标准 (EN 60950)的40 V产品型号
- 支持SCPI指令语言
- Windows操作程序下的LabView VIs & 控制软件

## 概要

EA-PS 9000 T系列是款由微处理器控制的实验室电源。它立足于用户友好的交互式操作概念, 配备一套完整的标准功能。其输出参数、监控功能与其它设定的配置很智能且舒适。

所有输出参数的监控功能, 可帮助用户减少测试设备, 且几乎可不用安装外部监控硬件与软件。

由两旋钮, 一个按键, 三个LED以及彩色触摸屏组成的控制面板, 显示所有关键数值与状态, 用户只需轻轻一点手指, 就可轻松操作本设备。

- Wide input voltage range 90...264 V with active PFC
- High efficiency up to 92%
- Output power ratings: 0...320 W up to 0...1500 W
- Output voltages: 0...40 V up to 0...500 V
- Output currents: 0...4 A up to 0...60 A
- Flexible, power regulated output stage
- Supervision (OVP, OCP, OPP)
- Overtemperature protection (OT)
- Intuitive touch panel with display for values, status and notifications
- USB port as standard, Ethernet & analog optional (all interfaces galvanically isolated)
- 40 V models compliant to SELV (EN 60950)
- SCPI command language supported
- LabView VIs & control software for Windows

## General

The microprocessor controlled laboratory power supplies of series EA-PS 9000 T offer a user-friendly, interactive handling concept, along with a extensive set of standard features, which can facilitate operating them. Configuration of output parameters, supervision features and other settings is smart and comfortable.

The implemented supervision features for all output parameters can help to reduce test equipment and make it almost unnecessary to install external supervision hardware and software.

The clear control panel with its two knobs, one pushbutton, three LEDs and the touch panel with colour display for all important values and status enable the user to handle the device easily with a few touches of a finger.

宥億企業股份有限公司

Tel: +886-2-7746-3368  
Fax: +886-2-2999-1178

地址:241 新北市三重區重新路五段 609 巷 16 號 8 樓之 10

YO IE ENTERPRISE CORP., LTD

E-mail: sales@yoie.com.tw  
Web: [www.yoie.com.tw](http://www.yoie.com.tw)

New Taipei City 241, Taiwan

Add: 8F-10, No.16, Ln. 609, Sec. 5, Chongxin Rd., Sanchong Dist.,

免責聲明 資料僅供參考, 若有與原廠不一處, 請以原廠規格為準, 且不供任何證明文件之用



# EA-PS 9000 T 320 W - 1500 W

## 交流输入


本系列采用主动式功率因数（简称：PFC），输入电压为90 V<sub>AC</sub>至264 V<sub>AC</sub>，适合全球范围内使用。1.5 kW的型号在供电电压<150 V<sub>AC</sub>时，输出功率自动减少到1 kW。

## AC input

The equipment uses an active Power Factor Correction (short: PFC), enabling worldwide use on a mains input from 90 V<sub>AC</sub> up to 264 V<sub>AC</sub>. Models with 1.5 kW will derate their output power to 1 kW below input voltages of 150 V<sub>AC</sub>.

## 功率级自动调整

本系列所有型号的输出功率都可灵活调整。可在较低电流时输出较高电压，或在低电压时输出较高电流，但总是维持在最大额定功率范围内。其最大设定功率可调，因此仅用一台产品就能覆盖广泛的应用。



## Auto-ranging power stage

All models are equipped with a flexible auto-ranging output stage which provides a higher output voltage at lower output current, or a higher output current at lower output voltage, always limited to the max. nominal output power. The maximum power set value is adjustable with these models. Therefore, a wide range of applications can already be covered by the use of just one unit.

## 直流输出

本系列有0...40 V和0...500 V输出电压，0...4 A和0...60 A输出电流，0...320 W和0...1500 W输出功率的不同型号。

因此不管是手动控制还是远程控制（模拟或数字），都可在0%与100%之间连续调节电流、电压与功率。它还有一内阻模式，能模拟一内部在线电阻。输出端位于产品后面板上。

## DC output

DC output voltages between 0...40 V and 0...500 V, output currents between 0...4 A and 0...60 A and output power ratings between 0...320 W and 0...1500 W are available.

Current, voltage and power can thus be adjusted continuously between 0% and 100%, no matter if manually or remotely controlled (analog or digital). The output terminals are located on the front side of the devices.

## 放电电路

额定输出电压为200 V或以上的产品，其输出电容都配有一放电电路。在空载或带小负载时，它能确保危险电压在直流输出关闭后降至60 V DC以下。该电压值被认为是对人体安全的最高电压。

## Discharge circuit

Models with a nominal output voltage of 200 V or higher include a discharge circuit for the output capacitors. For no load or low load situations, it ensures that the dangerous output voltage can sink to under 60 V DC after the DC output has been switched off. This value is considered as limit for voltages dangerous to human safety.

## 保护功能

为保护连接设备，可给产品设定一过压保护极限值(OVP)，以及过流(OCP)与过功率(OPP)保护极限值。

一旦因故超过这三个值中的一个，直流输出会被立即切断，并在显示器与接口端发出状态信号。本产品还有过温保护，如果产品过热，它会关断直流输出。

## Protective features

For protection of the equipment connected, it is possible to set an overvoltage protection threshold (OVP), as well as one for overcurrent (OCP) and overpower (OPP).

As soon as one of these thresholds is reached for any reason, the DC output will be immediately shut off and a status signal will be generated on the display and via the interfaces. There is furthermore an overtemperature protection, which will shut off the DC output if the device overheats.

## 远程感测


远程感测输入端可直接连到负载设备，以补偿连线上的部分压降。如果感测输入端已接到负载上，本电源会自动调整输出电压，以确保负载获得准确所需的电压值。

## Remote sensing

The standard sensing input can be connected directly to the load in order to compensate voltage drops along the cables. If the sensing input is connected to the load, the power supply will detect this and adjust the output voltage automatically to ensure the accurate required voltage is available at the load.

## 可选模拟接口

可以选择产品后板安装一电隔离模拟接口。该接口具有一模拟输入脚，接上0 V...10 V或0 V...5 V电压，可设置0...100%的输出电压、电流与功率。要监控输出电压与电流，可给模拟输出脚接上0 V...10 V或0 V...5 V来完成。此外，还有几个输入脚和输出脚，可用来控制和监控产品状态。




## Optional analog interface

A galvanically isolated analog interface can be installed optionally and subsequently, located on the rear of the device. It offers analog inputs to set voltage, current and power from 0...100% through control voltages of 0 V...10 V or 0 V...5 V. To monitor the output voltage and current there are analog outputs with 0 V...10 V or 0 V...5 V. Also, several inputs and outputs are available for controlling and monitoring the device status.

**EA-PS 9000 T 320 W - 1500 W**

显示器与控制面板



设定与实际输出电压、电流与功率都清晰显示于图形显示器上。彩色的TFT屏幕为点触式，用一个手指就能控制所有功能。

通过旋钮或者数字键盘直接输入参数，也可调节设定电压、电流或功率。

若想防止意外操作，可锁定所有操作键。

## Multi-language control panel



英文 / English



中文 / Chinese



俄文 / Russian



德文 / German

## 控制软件

本产品还配有适合Windows系统操作的控制软件，可远程控制多台同型产品，甚至不同型号产品。它有一个清晰的主界面，显示所有设定值与实际值，SCPI与ModBus RTU指令的直接输入模式，固件升级特性，以及被称为“排序”的半自动化控制表格。产品还可用注册码解锁，用“多功能控制”应用在一个窗口下一次性监控多达20台产品。此时还能使用排序与数据记录功能。

## Control software

Included with the device is a control software for Windows PC, which allows for the remote control of multiple identical or even different types of devices. It has a clear interface for all set and actual values, a direct input mode for SCPI and ModBus RTU commands, a firmware update feature and the semi-automatic table control named "Sequencing". Optionally unlockable with a licence code, the app "Multi Control" can monitor and control up to 20 units at once and in one windows. The sequencing feature and data logging are here available as well.

**宥億企業股份有限公司**Tel: +886-2-7746-3368  
Fax: +886-2-2999-1178

地址: 241 新北市三重區重新路五段 609 巷 16 號 8 樓之 10

**YO IE ENTERPRISE CORP., LTD**E-mail: sales@yoie.com.tw  
Web: [www.yoie.com.tw](http://www.yoie.com.tw)

New Taipei City 241, Taiwan




免責聲明 資料僅供參考，若有與原廠不合之處，請以原廠規格為準，且不供任何證明文件之用

**EA-PS 9000 T 320 W - 1500 W****输出值的预设**


设定输出值不会对输出状态有直接影响。它也会显示于显示器上，就在实际值下方。利用该特性，用户可通过旋钮或触摸屏上直接输入参数，预设所需的电压、电流和功率。还有5个用户配置文档，能让用户在常用设定值之间简便地转换，激活不同的配置文档即可完成。

**可选项**

- 带USB、以太网与模拟端口的可拆装接口模块（订购编号：33100231）

**Presetting of output values**

To set output values without a direct impact on the output condition, the set values are also shown on the display, positioned below the actual values. With this, the user can preset required values for voltage, current and power. It is either done by using the rotary knobs or by direct input on the touch panel. The five user profiles furthermore enable the user to switch easily between often used set values, just by activating a different user profile.

**产品图片****Product views**

后视图 (1000 W / 1500 W) / Rear view (1000 W / 1500 W)

**宥億企業股份有限公司**

Tel: +886-2-7746-3368  
Fax:+886-2-2999-1178

地址:241 新北市三重區重新路五段 609 巷 16 號 8 樓之 10

**YO IE ENTERPRISE CORP., LTD**

E-mail: [sales@yoie.com.tw](mailto:sales@yoie.com.tw)  
Web: [www.yoie.com.tw](http://www.yoie.com.tw)

New Taipei City 241, Taiwan  
Add: 8F.-10, No.16, Ln. 609, Sec. 5, Chongxin Rd., Sanchong Dist.,



**EA-PS 9000 T 320 W - 1500 W**

| 技术参数                              | Technical Data                             | Series EA-PS 9000 T / 系列   |                                    |
|-----------------------------------|--|--|------------------------------------|
| 交流: 供电                            | AC: Supply                                 |  |                                    |
| - 电压                              | - Voltage                                  | 90...264 V, 1ph+N  |                                    |
| - 频率                              | - Frequency                                | 45...65 Hz   |                                    |
| - 功率因数                            | - Power factor                             | >0.99  |                                    |
| - 功率降额                            | - Derating                                 | 仅针对1500 W型号: <150 V AC 降至 $P_{out\ max}$ 1000 W<br>Only models with 1500 W: <150 V AC to $P_{out\ max}$ 1000 W |                                    |
| 直流: 电压                            | DC: Voltage                                |  |                                    |
| - 精确度                             | - Accuracy                                 | <额定值的0.1% / <0.1% of rated value   |                                    |
| - 0-100%的负载调整率                    | - Load regulation 0-100%                   | <额定值的0.05% / <0.05% of rated value   |                                    |
| - $\pm 10\% \Delta U_{AC}$ 线性调整率  | - Line regulation $\pm 10\% \Delta U_{AC}$ | <额定值的0.02% / <0.02% of rated value   |                                    |
| - 带载10-100%调整需时                   | - Regulation 10-100% load                  | <2 ms  |                                    |
| - 带载10-90%上升时间                    | - Rise time 10-90%                         | 最大 / Max. 30 ms  |                                    |
| - 过压保护                            | - Overvoltage protection                   | 可调, 0...110% $U_{Nenn}$ / Adjustable, 0...110% $U_{Nenn}$  |                                    |
| 直流: 电流                            | DC: Current                                |  |                                    |
| - 精确度                             | - Accuracy                                 | <额定值的0.1% / <0.2% of rated value   |                                    |
| - 1-100% $\Delta I_{DC}$ 的负载调整率   | - Load regulation 1-100% $\Delta I_{DC}$   | <额定值的0.15% / <0.15% of rated value   |                                    |
| - $\pm 10\% \Delta U_{AC}$ 的线性调整率 | - Line regulation $\pm 10\% \Delta U_{AC}$ | <额定值的0.05% / <0.05% of rated value   |                                    |
| 直流: 功率                            | DC: Power                                  |  |                                    |
| - 精确度                             | - Accuracy                                 | <额定值的1% / <1% of rated value   |                                    |
| 过压类别                              | Overvoltage category                       | 2  |                                    |
| 保护功能                              | Protection                                 | OT, OVP, OCP, OPP, PF <sup>12</sup>  |                                    |
| 隔离耐压                              | Insulation                                 |  |                                    |
| - 交流输入对外壳                         | - AC input to enclosure                    | 2500 V DC  |                                    |
| - 交流输入对直流输出                       | - AC input to DC output                    | 2500 V DC  |                                    |
| - 直流输出对外壳 (PE)                    | - DC output to enclosure                   | 负极: 最大400 V DC, 正极: 最大400 V DC + 输出电压 /<br>Negative: max. 400 V DC, positive: max. 400 V DC + output voltage   |                                    |
| 污染等级                              | Degree of pollution                        | 2  |                                    |
| 保护等级                              | Protection class                           | 1  |                                    |
| 模拟接口                              | Analog interface                           | 可选 (15-针D-Sub母插, 电隔离) /<br>optionally available (15-pole D-Sub, galvanically isolated)                         |                                    |
| - 信号范围                            | - Signal range                             | 0..5 V 或 0..10 V (可切换) / 0..5 V or 0..10 V (switchable)  |                                    |
| - 输入脚                             | - Inputs                                   | U, I, P, 远程开-关, 直流输出开-关 /<br>U, I, P, Remote on-off, DC output on-off  |                                    |
| - 输出脚                             | - Outputs                                  | U/I, 过压, 报警, 参考电压 /<br>U/I, Overvoltage, alarms, reference voltage   |                                    |
| - U/I/P精确度                        | Accuracy U/I/P                             | 0..10 V: <0.2%      0..5 V: <0.4%  |                                    |
| 并联操作                              | Parallel operation                         | 可实现 / Possible   |                                    |
| 安规标准                              | Standards                                  | EN 60950, EN 61326, EN 61010, EN 55022 等级 B / Class B  |                                    |
| 制冷方式                              | Cooling                                    | 温控风扇 / Temperature controlled fan  |                                    |
| 工作温度                              | Operation temperature                      | 0...50 °C  |                                    |
| 储存温度                              | Storage temperature                        | -20...70 °C  |                                    |
| 相对湿度                              | Relative humidity                          | <80%, 无凝露 / non-condensing   |                                    |
| 工作高度                              | Operation altitude                         | <2000 m  |                                    |
| 机械结构                              | Mechanics                                  |  |                                    |
| - 重量                              | - Weight                                   | 320 W - 640 W: ~ 7 kg  | 1000 W - 1500 W: ~ 8 kg            |
| - 尺寸 (宽x高x深) <sup>1</sup>         | - Dimensions (W x H x D) <sup>1</sup>      | 320 W - 640 W: 92 x 239 x 352 mm   | 1000 W - 1500 W: 92 x 239 x 412 mm |

<sup>1</sup> 仅为机身尺寸 / Body only  
<sup>2</sup> 也可见第146页 / See page 146

# 宥億企業股份有限公司

Tel: +886-2-7746-3368  
Fax: +886-2-2999-1178

地址: 241 新北市三重區重新路五段 609 巷 16 號 8 樓之 10

# YO IE ENTERPRISE CORP., LTD

E-mail: sales@yoie.com.tw  
Web: www.yoie.com.tw

New Taipei City 241, Taiwan  
Add: 8F.-10, No.16, Ln. 609, Sec. 5, Chongxin Rd., Sanchong Dist.

免責聲明 資料僅供參考，若有與原廠不一處，請以原廠規格為準，且不供任何證明文件之用




**EA-PS 9000 T 320 W - 1500 W**

| 型号<br>Model | 电压<br>Voltage | 电流<br>Current | 功率<br>Power | 效率<br>Efficiency | U的纹波 <sup>(2)</sup><br>Ripple U <sup>(2)</sup> | I的纹波<br>Ripple I      | 编程 <sup>(1)</sup><br>Programming |          |          | 订购编号<br>Ordering number |
|-------------|---------------|---------------|-------------|------------------|--|-----------------------|----------------------------------|----------|----------|-------------------------|
|             |               |               |             |                  |  |                       | U (typ.)                         | I (typ.) | P (typ.) |                         |
| PS 9040-20T | 0...40 V      | 0...20 A      | 0...320 W   | ≤88%             | 20 mV <sub>PP</sub> / 2 mV <sub>RMS</sub>      | 1 mA <sub>RMS</sub>   | 1.5 mV                           | 0.8 mA   | 0.012 W  | 06200440                |
| PS 9080-10T | 0...80 V      | 0...10 A      | 0...320 W   | ≤89%             | 20 mV <sub>PP</sub> / 2 mV <sub>RMS</sub>      | 1 mA <sub>RMS</sub>   | 3.1 mV                           | 0.4 mA   | 0.012 W  | 06200441                |
| PS 9200-04T | 0...200 V     | 0...4 A       | 0...320 W   | ≤89%             | 50 mV <sub>PP</sub> / 6 mV <sub>RMS</sub>      | 1.5 mA <sub>RMS</sub> | 7.6 mV                           | 0.2 mA   | 0.012 W  | 06200442                |
| PS 9040-40T | 0...40 V      | 0...40 A      | 0...640 W   | ≤89%             | 20 mV <sub>PP</sub> / 2 mV <sub>RMS</sub>      | 1 mA <sub>RMS</sub>   | 1.5 mV                           | 1.5 mA   | 0.024 W  | 06200443                |
| PS 9080-20T | 0...80 V      | 0...20 A      | 0...640 W   | ≤91%             | 20 mV <sub>PP</sub> / 2 mV <sub>RMS</sub>      | 1 mA <sub>RMS</sub>   | 3.1 mV                           | 0.8 mA   | 0.024 W  | 06200444                |
| PS 9200-10T | 0...200 V     | 0...10 A      | 0...640 W   | ≤92%             | 50 mV <sub>PP</sub> / 6 mV <sub>RMS</sub>      | 1.5 mA <sub>RMS</sub> | 7.6 mV                           | 0.4 mA   | 0.024 W  | 06200445                |
| PS 9040-40T | 0...40 V      | 0...40 A      | 0...1000 W  | ≤92%             | 25 mV <sub>PP</sub> / 4 mV <sub>RMS</sub>      | 6 mA <sub>RMS</sub>   | 1.5 mV                           | 1.5 mA   | 0.038 W  | 06200446                |
| PS 9080-40T | 0...80 V      | 0...40 A      | 0...1000 W  | ≤92%             | 25 mV <sub>PP</sub> / 4 mV <sub>RMS</sub>      | 6 mA <sub>RMS</sub>   | 3.1 mV                           | 1.5 mA   | 0.038 W  | 06200447                |
| PS 9200-15T | 0...200 V     | 0...15 A      | 0...1000 W  | ≤93%             | 150 mV <sub>PP</sub> / 23 mV <sub>RMS</sub>    | 1.8 mA <sub>RMS</sub> | 7.6 mV                           | 0.6 mA   | 0.038 W  | 06200448                |
| PS 9500-06T | 0...500 V     | 0...6 A       | 0...1000 W  | ≤93%             | 155 mV <sub>PP</sub> / 33 mV <sub>RMS</sub>    | 8 mA <sub>RMS</sub>   | 19.1 mV                          | 0.2 mA   | 0.038 W  | 06200449                |
| PS 9040-60T | 0...40 V      | 0...60 A      | 0...1500 W  | ≤92%             | 25 mV <sub>PP</sub> / 4 mV <sub>RMS</sub>      | 6 mA <sub>RMS</sub>   | 1.5 mV                           | 2.3 mA   | 0.057 W  | 06200450                |
| PS 9080-60T | 0...80 V      | 0...60 A      | 0...1500 W  | ≤92%             | 25 mV <sub>PP</sub> / 4 mV <sub>RMS</sub>      | 6 mA <sub>RMS</sub>   | 3.1 mV                           | 2.3 mA   | 0.057 W  | 06200451                |
| PS 9200-25T | 0...200 V     | 0...25 A      | 0...1500 W  | ≤93%             | 150 mV <sub>PP</sub> / 23 mV <sub>RMS</sub>    | 1.8 mA <sub>RMS</sub> | 7.6 mV                           | 1 mA     | 0.057 W  | 06200452                |
| PS 9500-10T | 0...500 V     | 0...10 A      | 0...1500 W  | ≤93%             | 155 mV <sub>PP</sub> / 33 mV <sub>RMS</sub>    | 8 mA <sub>RMS</sub>   | 19.1 mV                          | 0.2 mA   | 0.057 W  | 06200453                |

(1) 忽略产品错误时的可编程分辨率 / Programmable resolution disregarding device errors

(2) RMS值：在BWL 300 kHz时测量的LF值，PP值：在BWL 20MHz时测量的HF值 / RMS value: measures at LF with BWL 300 kHz, PP value: measured at HF with BWL 20MHz

**宥億企業股份有限公司**Tel: +886-2-7746-3368  
Fax: +886-2-2999-1178

地址: 241 新北市三重區重新路五段 609 巷 16 號 8 樓之 10

**YO IE ENTERPRISE CORP., LTD**E-mail: sales@yoie.com.tw  
Web: [www.yoie.com.tw](http://www.yoie.com.tw)

Add: 8F.-10, No.16, Ln. 609, Sec. 5, Chongxin Rd., Sanchong Dist., New Taipei City 241, Taiwan

免責聲明 資料僅供參考，若有與原廠不合之處，請以原廠規格為準，且不供任何證明文件之用

