

1
Component
Tester

LCR Meter 6365/6366/6367



CE RS232 Remote GPIB Option

Key Feature

- Basic accuracy up to $\pm 0.08\%$
- The lowest test frequency from 0.1Hz (636XA series)
- Synchronous tests with four parameter settings
- User-friendly interface, easy to operate
- Support fully test functions
- Interface: GPIB, RS232, Handler and USB
- 7 inch 800*480, TFT LCD color screen
- Multi step function

Accessory

Standard	Optional
Power Code	F423503
User Manual CD	F423903
F423501	F423905

Measuring Range

IZI, R, X	0.001m Ω - 99.999M Ω	Q	0.1 - 9999.9
IYI, G, B	0.1nS - 99.999S	DCR	0.001m Ω - 99.999M Ω
Cs Cp	0.01pF - 9.9999F	Δ %	-9999% - 9999%
Ls Lp	0.1nH - 99.999kH	θ	-180° - + 180°
D	0.00001 - 9.9999		



Specification

Model Name	6365	6366	6367
Test Frequency	10Hz-200kHz	10Hz-500kHz	10Hz-1MHz
Model Name	6365A	6366A	6367A
Test Frequency	0.1Hz-200kHz	0.1Hz-500kHz	0.1Hz-1MHz
Points Of Test Frequency	Continuity		
Basic Accuracy	± 0.08%		
AC Drive Level	10mV to 2Vrms (1m Vrms solution)		
DC Drive Level	0.01V-2V		
Output Impedance	100Ω		
Frequency trimming resolution	5 Digits		
Frequency output accuracy	±0.01%		
AC/DC test speed	8mS		

Component Tester

General

Measured Value Detection Mode	Define upper and lower thresholds according to main and sub parameters
ESR	Series/Parallel
Test Mode	Meter mode/Multi-step mode
Test Range	Automatic/Lock
Multi-step test	MAX, 8 step
Calibration	Open Circuit / Short Circuit: Avoid the misreading caused by the stray capacitance from kelvin clips and fixtures
Auto-save when power-off function	When the power is turned off or encounter a power outage, all the data will be saved automatically and recovered when tester system is switched on again
Power Supply	Voltage 90-132Vac or 198-264Vac (selectable) Frequency 47 ~ 63Hz
Display	800*480 Color Screen, 7" TFT
Interface	RS-232、 GPIB、 GPIB、 Handler
Flash Memory	Built-in flash for storage of 128 groups of Multi-steps setting
Operation	Auto、 Manual、 RS-232、 GPIB、 Handler
Environment	Temperature : 10° C ~ 40° C、 Humidity : 20 ~ 90%RH
Dimension (W*H*D)	344x145x343 mm
Weight	3 Kg

育億企業股份有限公司

YO IE ENTERPRISE CORP., LTD

Tel: +886-2-7746-3368
Fax: +886-2-2999-1178

E-mail: sales@yoie.com.tw
Web: www.yoie.com.tw

New Taipei City 241, Taiwan

地址: 241 新北市三重區重新路五段 609 巷 16 號 8 樓之 10

Add: 8F.-10, No.16, Ln. 609, Sec. 5, Chongxin Rd., Sanzhong Dist.,

